

H24

HEAT CABIN
24HP (Hydrostatic)



SPECIFICATIONS

FEATURES	H24 HEAT CABIN
ENGINE	
Engine Model	Mitsubishi S3L2
HP Category	24
No. of Cylinder	3
Aspiration	Natural
Cubic Capacity (Cl)	80
Rated RPM	2500
Max. Torque	76Nm@2000
TRANSMISSION	
Drive	4WD
Forward/Reverse Controls	Twin Touch Pedals
Gearbox	HST (2 Range)
Transmission Type	Constant Mesh
Cruise Control	Yes
BRAKES	
Type	Oil Immersed Brakes
Type of Actuation	Mechanical, Foot Operated
Differential Lock	Standard
PTO	
PTO (RPM)	Rear - 540 & 2451 Mid PTO - 2100 & 2438
PTO Clutch	Wet Type
PTO Actuation	Button Operated
Steering	Power Steering
HYDRAULICS	
3 Point Linkages	CAT-1IN
3 Point Lifting Capacity @ ball ends (lbs)	1323
Aux Hydraulic Circuit	1DA (Detent with Float)
Total Hydraulic Flow (GPM)	3
CAPACITY	
Fuel Tank (Gal)	7
DIMENSIONS & WEIGHT (AGRI TIRES)	
Weight (lbs)	3108
Wheel Base (in)	61
Total Length with TPL (in)	112
Total Width (in)	47
Height (in) upto ROPS	93
Ground Clearance	9 (Front Axle)

FEATURES

ENGINE	
Engine Model	Mitsubishi S3L2
HP Category	24
No. of Cylinder	3
Aspiration	Natural
Cubic Capacity (Cl)	80
Rated RPM	2500
Max. Torque	76Nm@2000
TRANSMISSION	
Drive	4WD
Forward/Reverse Controls	Twin Touch Pedals
Gearbox	HST (2 Range)
Transmission Type	Constant Mesh
Cruise Control	Yes
BRAKES	
Type	Oil Immersed Brakes
Type of Actuation	Mechanical, Foot Operated
Differential Lock	Standard
PTO	
PTO (RPM)	Rear - 540 & 2451 Mid PTO - 2100 & 2438
PTO Clutch	Wet Type
PTO Actuation	Button Operated
Steering	Power Steering
HYDRAULICS	
3 Point Linkages	CAT-1IN
3 Point Lifting Capacity @ ball ends (lbs)	1323
Aux Hydraulic Circuit	1DA (Detent with Float)
Total Hydraulic Flow (GPM)	3
CAPACITY	
Fuel Tank (Gal)	7
DIMENSIONS & WEIGHT (AGRI TIRES)	
Weight (lbs)	3108
Wheel Base (in)	61
Total Length with TPL (in)	112
Total Width (in)	47
Height (in) upto ROPS	93
Ground Clearance	9 (Front Axle)

TECHNICAL SPECIFICATION

ENGINE	
Engine Model	Mitsubishi S3L2
HP Category	24
No. of Cylinder	3
Aspiration	Natural
Cubic Capacity (Cl)	80
Rated RPM	2500
Max. Torque	76Nm@2000
TRANSMISSION	
Drive	4WD
Forward/Reverse Controls	Twin Touch Pedals
Gearbox	HST (2 Range)
Transmission Type	Constant Mesh
Cruise Control	Yes
BRAKES	
Type	Oil Immersed Brakes
Type of Actuation	Mechanical, Foot Operated
Differential Lock	Standard
PTO	
PTO (RPM)	Rear - 540 & 2451 Mid PTO - 2100 & 2438
PTO Clutch	Wet Type
PTO Actuation	Button Operated
Steering	Power Steering
HYDRAULICS	
3 Point Linkages	CAT-1IN
3 Point Lifting Capacity @ ball ends (lbs)	1323
Aux Hydraulic Circuit	1DA (Detent with Float)
Total Hydraulic Flow (GPM)	3
CAPACITY	
Fuel Tank (Gal)	7
DIMENSIONS & WEIGHT (AGRI TIRES)	
Weight (lbs)	3108
Wheel Base (in)	61
Total Length with TPL (in)	112
Total Width (in)	47
Height (in) upto ROPS	93
Ground Clearance	9 (Front Axle)

*Data and specifications are subject to change without any reference notice due to continuous product improvement and development. All dimensions are with standard tires.